

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/031326 A1

(51) International Patent Classification⁷: **G01N 21/896**,
G01B 11/30

93 Linköping (SE). **GÖKSTORP, Mats** [SE/SE]; An-
nelundsbacken 6, S-590 77 Vreta Kloster (SE).

(21) International Application Number:
PCT/SE2004/001375

(74) Agent: **STRÖM & GULLIKSSON IP AB**; Wallenbergs
gata 4, S-583 35 Linköping (SE).

(22) International Filing Date:
24 September 2004 (24.09.2004)

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0302603-6 1 October 2003 (01.10.2003) SE

(71) Applicant (for all designated States except US): **SICK
IVP AB** [SE/SE]; Wallenbergs gata 4, S-583 35 Linköping
(SE).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JOHANNES-
SON, Mattias** [SE/SE]; Landeryd Sörholmen 2, S-585

[Continued on next page]

(54) Title: SYSTEM AND METHOD OF IMAGING THE CHARACTERISTICS OF AN OBJECT



(57) Abstract: A system and method for imaging the characteristics of an object (2) having at least a first (2a) and a second (2b) layer. The object (2) is illuminated by means of incident light (4), and light (5b) reflected from the object (2) is detected by means of an imaging sensor (6) in which the detected light is converted into electrical charges, according to which a representation of the object (2) is created. Information on light scattered (5a) in the first layer (2a) and the second layer (2b) of the object (2) is obtained from the representation and this information is compared to stored information in order to detect defects on the object (2).

WO 2005/031326 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*